

EonStor[®] A12E-G2121

2U-Profile, iSCSI to SATA-II
Cost-effective iSCSI RAID Storage



HIGHLIGHTS

- Shared storage over standard Ethernet networks
- Compliant with IETF iSCSI standard (RFC 3720)
- CHAP authentication security
- 12 drive bays for 3Gbps, SATA-II disk drives
- Storage volumes presented via SCSI-like ID/LUN mapping as iSCSI targets
- High density 2U chassis providing up to 4.8TB storage capacity
- Optional BBU for protection of cached data
- Dual-speed fans to reduce system noise
- Real-time event notification by a variety of methods

OVERVIEW

The EonStor A12E-G2121 provides cost-effective storage by combining Infotrend's sophisticated RAID technology with iSCSI protocol that encapsulates SCSI data blocks and carries them over standard Ethernet infrastructures. Access to its storage volumes is made with connectivity of two 1Gbps Ethernet (GbE) ports via familiar Gigabit Ethernet using standard copper cabling or point-to-point to application hosts.

The A12E storage array is ideal for building a shared storage pool for disk-to-disk volume distribution, backup, storage consolidation, and replication of data among networked servers. The storage array operates with the advantages of iSCSI protocol in terms of its block-based performance, lower training and maintenance costs without the complexity of other networking technologies such as Fibre Channel.

The EonStor A12E-G2121 is built around Infotrend's next-generation, custom-built ASIC266 XOR engine. Boasting a 2GB/sec internal bandwidth, the architecture features the PowerPC CPU and the dual PCI/PCI-X buses for fast I/O transactions.

HIGH PERFORMANCE

Featuring a 64-bit 133MHz data bus, the subsystem's high data throughput is more than sufficient for small-to-medium sized servers or workstations. Robust functionality and adaptive algorithms facilitate chip-level operation that is already fast and flexible. For example, a timeout can be configured for individual drive response time. If a specific disk drive fails to respond in time, the firmware accumulates data from the adjacent stripes of the array to satisfy applications that require fast return of data.

These adaptive designs assure sufficient throughput for a wide range of applications running on Windows 2000/2003/XP, Linux, or Unix-based servers. Ideal applications include Disk-to-Disk backup, small business network, storage consolidation and others.

ENCLOSURE MANAGEMENT

The EonStor A12E-G2121 subsystem incorporates massive storage capacity in a safe environment where a variety of hardware and firmware mechanisms ensure the highest level of data availability. In addition to RAID protection for the disk drives, the PSUs and cooling modules come implemented as redundant/hot-swappable modules. Even the battery module can be replaced online.

The rotation speed of the enclosure's dual-speed fans is controlled by the firmware. In critical conditions, e.g., PSU or fan failure, the fan rotation speed is raised to a higher level. Control over caching behaviors is a user-configurable option. In the event of component failures, such as UPS failure or low battery charge, the firmware stops caching write requests in cache memory.

EonStor® A12E-G2121

**2U-Profile, iSCSI to SATA-II
Cost-effective iSCSI RAID
Storage**

TASK SCHEDULER

Media Scan is now armed with a unique function that helps repair media errors on drives. By combining the Task Scheduler with Media Scan, the scanning operation can be scheduled to begin at a specified start time and repeated at configured intervals. This hands-free operation allows each such schedule to be defined to operate on individual hard drives, all drives of a certain class, all member drives of a specified logical drive, or all member drives of all logical drives.

SPECIFICATIONS

RAID CONTROLLER

- 600MHz RISC processor with 512KB embedded L2 cache
- Infotrend custom-built ASIC266 with XOR engine and ECC support
- Standard 512MB cache memory in one DDR RAM DIMM with optional BBU
- System Voltage/Temperature self-monitoring
- One RS-232C (Audio Jack) serial port, for text mode management
- Two 1Gbps Ethernet ports
- Audible alarm

RAID OPERATION

- RAID level 0, 1 (0+1), 3, 5, 10, 30, 50, JBOD and RAID
- Hot-spare drive operation
- Drive hot-swapping
- Automatic background rebuild
- Online expansion

HOST INTERFACES

- Two 1Gbps Ethernet

MANAGEMENT SOFTWARE

- GUI, Telnet, and SSH system monitoring via Ethernet
- RAIDWatch manager software for Windows and Linux platforms
- Firmware-embedded manager via RS-232C (Audio Jack) (platform independent)
- Widest range of event notification methods, including Email, LAN broadcast, Fax, SNMP Traps, SMS, MSN, and ICQ

EXTERNAL CONNECTIONS

- Two RJ-45 Ethernet ports
- One Audio Jack serial port connector (38400, n, 8, 1)

ENCLOSURE DIMENSIONS

- 2U, 19-inch rackmount chassis
- Chassis without forearm handles:
446(W) x 88(H) x 490(D) mm
- Chassis with forearm handles:
482(W) x 88(H) x 505(D) mm

Copyright © 2005 by Infotrend Technology, Inc. All rights reserved.

- Any information provided herein is without warranties of any kind and is subject to change by Infotrend without prior notice.
- Infotrend offers a 3-year limited warranty on subsystems and a 1-year warranty on battery backup units.
- Infotrend and the Infotrend logo are registered trademarks of Infotrend Technology, Inc.
- EonStor and RAIDWatch are trademarks or registered trademarks of Infotrend Technology, Inc.
- All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.



Asia Pacific
International Headquarters
Infotrend Technology, Inc.
8F, No. 102 Chung-Shan Rd., Sec. 3
Chung-Ho City, Taipei Hsien, Taiwan
Tel: +886-2-2226-0126
Fax: +886-2-2226-0020
sales.ap@infotrend.com
support.ap@infotrend.com
http://esupport.infotrend.com.tw
http://www.infotrend.com

Americas
Infotrend Corporation
2200 Zanker Road, Unit D,
San Jose, CA. 95131, USA
Tel: +1-408-988-5088
Fax: +1-408-988-6288
sales.us@infotrend.com
http://esupport.infotrend.com
http://www.infotrend.com/americas

Europe
Infotrend Europe Limited
1 Cherrywood, Stag Oak Lane
Chineham Business Park
Basingstoke, Hampshire
RG24 8WF, UK
Tel: +44-1256-707-700
Fax: +44-1256-707-889
sales.eu@infotrend.com
support.eu@infotrend.com
http://esupport.infotrend-europe.com
http://www.infotrend.com/europe

China
Infotrend Technology, Limited
Room 1210, West Wing, Tower One,
Junefield Plaza, No. 6 Xuanwumen Street,
Xuanwu District, Beijing, China.
Post code: 100052
Tel: +86-10-63106168
Fax: +86-10-63106188
sales.cn@infotrend.com
support.cn@infotrend.com
http://esupport.infotrend.com.tw
http://www.infotrend.com/china

Japan
Infotrend Japan, Inc.
6F, Okayasu Bldg.,
1-7-14 Shibaura Minato-ku,
Tokyo, 105-0023 Japan
Tel: +81-3-5730-6551
Fax: +81-3-5730-6552
sales.jp@infotrend.com
support.jp@infotrend.com
http://esupport.infotrend.com.tw
http://www.infotrend.com/japan